

Specifications

Sunlift

SunLift Model	SL2006AR	SL2008AR	SL3010	SL4010AR	SL6012AR	SL8012ER	SL10014ER	SL12018ER	SL18020ER	SL24022ER
Capacity (pounds)	2,000	2,000	3,000	4,000	6,000	8,000	10,000	12,000	18,000	24,000
Lifting Ranges*	<u>36</u> "/48"/60"	<u>36</u> "/48"/60"	<u>48</u> "	<u>36</u> "/ <u>48</u> "/60"/(72")	<u>36</u> "/ <u>48</u> "/60"/(72")	<u>60</u> "/(72"**)	<u>60</u> "/(72"**)	<u>60</u> "/(72"**)	<u>60</u> "/(72"**)	<u>60</u> "/(72"**)
Capacity at Max. Lifting Range	1,800	1,800	3,000	4,000	4,500	8,000	9,500	9,500	14,250	19,000
Bunk Length	6'	8'	10'	10'	12'	12'	14'	18'	20'	22'
Frame Length	95"	95"	10'5"	10'5"	12'5"	12'5"	14'5"	18'5"	20'5"	24'
Frame Width	5'6"	5'6"	9'6"	9'6"	10'	11'	11'	11'	12'6"	12'6"
Weight (pounds)	200	210	450	550	655	1,000	1,050	1,500	2,000	2,500
Lifting Speed (Typ.)	15 sec	15 sec	15 sec	25 sec	35 sec	50 sec	50 sec	50 sec	55 sec	60 sec
Min. Water Depth Required (Typ.)	18"	18"	23"	25"	27"	36"	40"	44"	50"	62"
Min. Depth w/Shallow Water Roller (Typ.)	N/A	N/A	N/A	16"	17"	30"	34"	38"	N/A	N/A
Remote Control	Opt.	Opt.	Opt.	Std.	Std.	Std.	Std.	Std.	Std.	Std.
Leg Lengths Available	2'-6'	2'-6'	2'-24'	2'-24'	2'-24'	2'-24'	2'-24'	2'-24'	2'-24'	2'-14'

Available Canopies	P1260†	P1260†	P22108 H24108	P22108 H24108	P24114 H24108	P27126 P30126 P36126 P42126	P27126 P30126 P36126 P42126	P27126 P30126 P36126 P42126	Custom	Custom
--------------------	--------	--------	------------------	------------------	------------------	--------------------------------------	--------------------------------------	--------------------------------------	--------	--------

*Some lifting ranges require optional lifting arms, standard ranges are shown with underline (Example: 36") Special order Model 72" XR Range. † Special Order ONLY

Special Model Numbers – SLX8012SR, SL9514SR, SL9518XR, SI142209XR, SL19022XR